

529448

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



28 MAR 2005



(43) International Publication Date
22 April 2004 (22.04.2004)


PCT

(10) International Publication Number
WO 2004/033250 A2

- (51) International Patent Classification⁷: **B60N 2/00**
- (21) International Application Number: PCT/US2003/031494
- (22) International Filing Date: 3 October 2003 (03.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/416,336 4 October 2002 (04.10.2002) US
- (71) Applicant (for all designated States except US): **JOHNSON CONTROLS TECHNOLOGY COMPANY** [US/US]; 650 Waverly, Holland, MI 49423 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **SEIBOLD, Kurt, A.** [US/US]; 11896 Fair Way Drive, South Lyon, MI 48178 (US).
- (74) Agent: **LAZARUS, John, M.**; Foley & Lardner, 777 E. Wisconsin Avenue, 33rd Floor, Milwaukee, WI 53202 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: RECLINER MECHANISM



(57) Abstract: A recliner mechanism for a vehicle seat includes a toothed sector member secured to a seat frame and first and second pivoted pawl members each including a plurality of teeth to engage the teeth of the sector member. The first and second pawl members also each pivot on a cam pin member located at a distal end thereof, the cam pins each have a center axis and an offset axis having by a toothed cam lobe. The toothed cam lobes mesh such that rotation of one cam pin member causes the other cam pin member to rotate in the opposite direction. A handle is coupled to at least one of the cam pin members to rotate the cam pin members and cause the pawl members to rotate about a pin connecting the proximal ends of the pawl members. The pawl members are movable between a first or locked position and a second or unlocked position, permitting the seat back to be adjusted with respect to the seat base against the force of a spring.

WO 2004/033250 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.